



AIRY-WB900-5K

COMMANDO AirY 900Mbps, 5.8GHz, 15dBi,
802.11ac Wave 2, P2P/P2MP, 5KM Wireless
Bridge

Contents

Product Overview

Product Highlights

Features and Benefits

Software

Hardware

Specifications

Support & Warranty

Ordering Information

Document History

Product Overview

COMMANDO AIRY-WB900-5K is a high-performance 5.8GHz Outdoor Wireless Bridge designed to provide reliable long-distance wireless connectivity for surveillance systems, industrial facilities, campuses, warehouses, and remote network deployments. Based on IEEE 802.11ac Wave 2 technology, it delivers a maximum wireless throughput of up to 867Mbps.

Equipped with a built-in 15dBi high-gain directional antenna, the AIRY-WB900-5K supports wireless transmission distances of up to 5KM, making it ideal for Point-to-Point (P2P) and Point-to-Multipoint (P2MP) wireless bridge deployments. The device also supports intelligent channel analysis and automatic optimal channel selection to help maintain stable wireless performance in outdoor environments.

Powered by powerful hardware platform with 128MB DDR2 memory and 16MB Flash, the AIRY-WB900-5K provides dependable performance for demanding outdoor networking applications. It features one Gigabit WAN port with 12V Passive PoE support and one Gigabit LAN port, enabling reliable wired connectivity and simplified installation.

Designed for outdoor deployment, the AIRY-WB900-5K features an IP65-rated enclosure, built-in ESD and surge protection, one-button pairing, and support for AP Mode and Repeater Mode, making it a dependable and cost-effective solution for long-distance outdoor wireless networking.

Product Highlights

- Delivers high-performance 5.8GHz wireless connectivity with wireless data rates of up to 867Mbps based on IEEE 802.11ac Wave 2 technology.
- Supports Point-to-Point (P2P) and Point-to-Multipoint (P2MP) wireless bridge deployments with transmission distances of up to 5KM.
- Equipped with a built-in 15dBi high-gain directional antenna for stable long-distance wireless communication.
- Features 1 × Gigabit WAN port with 12V Passive PoE and 1 × Gigabit LAN port for high-speed wired connectivity.
- Supports 12~48V Passive PoE and 12V DC power input for flexible deployment in various outdoor environments.
- Supports AP Mode and Repeater Mode for flexible wireless bridge deployment and network expansion.
- Supports up to 4 SSIDs, Wireless MAC Filtering (Whitelist), Wireless Isolation, RF Power Adjustment, and VLAN Configuration for enhanced network management and security.
- Supports intelligent channel analysis, automatic optimal channel selection, and one-button pairing for simplified deployment and improved wireless performance.
- Supports up to 64 wireless clients, making it suitable for surveillance, industrial, campus, and remote networking applications.
- Industrial-grade IP65-rated outdoor enclosure with ESD and surge protection for reliable operation in harsh outdoor environments.

Features and Benefits

Long-Distance Wireless Connectivity

The COMMANDO AIRY-WB900-5K is designed for reliable long-range outdoor wireless communication. Equipped with a built-in 15dBi high-gain directional antenna, it supports wireless transmission distances of up to 5KM, making it ideal for building-to-building connectivity, CCTV surveillance backhaul, industrial networking, campus connectivity, and remote site interconnection.

High-Speed Wireless Performance

Based on IEEE 802.11ac Wave 2 technology, the AIRY-WB900-5K delivers wireless speeds of up to 867Mbps, providing reliable transmission of voice, video, and data across long-distance wireless links.

Point-to-Point and Point-to-Multipoint Deployment

Supports both:

- Point-to-Point (P2P)
- Point-to-Multipoint (P2MP)

This enables flexible deployment across various outdoor wireless bridge applications.

Intelligent Channel Optimization

Supports intelligent channel analysis and automatic optimal channel selection, helping reduce wireless interference and improve link stability in challenging RF environments.

One-Button Pairing

Supports one-button pairing, simplifying wireless bridge deployment and reducing installation time and configuration complexity.

Flexible Operating Modes

Supports:

- AP Mode
- Repeater Mode

These operating modes provide deployment flexibility for different outdoor networking scenarios.

Gigabit Wired Connectivity

Equipped with:

- 1 × Gigabit WAN Port with 12V Passive PoE
- 1 × Gigabit LAN Port

These interfaces provide reliable high-speed wired connectivity while enabling simplified installation through PoE support.

Advanced Wireless Management

Supports:

- Up to 4 SSIDs
- Hidden SSID
- Relay Function
- WiFi Timing ON/OFF
- RF Power Adjustment
- Wireless Client Limitation
- Intelligent Channel Analysis
- Automatic Optimal Channel Selection

These features help optimize wireless performance and simplify network administration.

Enhanced Wireless Security

Provides multiple security mechanisms including:

- NONE (Open)
- WPA/WPA2-PSK (TKIP/AES)
- EAP Authentication

Additional security features include:

- Wireless MAC Address Filtering (Whitelist)
- Wireless Isolation
- AP Internal Isolation

These features help secure wireless communications and control network access.

Reliable Outdoor Design

Featuring an IP65-rated enclosure, the AIRY-WB900-5K is designed to operate reliably in outdoor environments exposed to dust and water.

Industrial-Grade Protection

The device incorporates built-in protection mechanisms including:

- **ESD Protection**
 - Air: $\pm 8\text{KV}$
 - Touch: $\pm 6\text{KV}$
- **Electrical Surge Protection**
 - Common Mode: 2KV
 - Differential Mode: 1KV

These protection features help improve reliability in outdoor deployments.

Energy-Efficient Operation

With power consumption of less than 10W, the AIRY-WB900-5K delivers reliable long-distance wireless performance while maintaining low energy consumption.

Cost-Effective Wireless Bridge Solution

Combining 5KM wireless transmission, 15dBi directional antenna, P2P/P2MP support, Gigabit connectivity, one-button pairing, and IP65 protection, the COMMANDO AIRY-WB900-5K provides a reliable and cost-effective solution for long-distance outdoor wireless networking applications.

This section is fully aligned with the AIRY-WB900-5K specification sheet and covers all major hardware and wireless capabilities without introducing features that are not listed.

Software

COMMANDO AIRY-WB900-5K provides comprehensive standalone management through an intuitive WEB GUI interface, enabling easy configuration, monitoring, security management, and maintenance for long-distance outdoor wireless bridge deployments.

Monitoring

Provides real-time monitoring of:

- System Information
- Device Status
- Wireless Status
- Network Status
- Connected Wireless Clients
- Running Status

These monitoring features help administrators quickly assess device health and network performance.

System Setup

Supports:

- Configuration Backup
- Configuration Restore
- Restore Factory Settings
- Firmware Upgrade
- Scheduled Restart
- Immediate Restart
- Time Management

- Time Synchronization
- System Log

These features simplify device maintenance and long-term management.

Network Management

Supports:

- DHCP Server
- VLAN Configuration

These networking features enable flexible deployment and efficient network segmentation.

Wireless Management

Operating Modes

Supports:

- AP Mode
- Repeater Mode

Wireless Features

- Up to 4 SSIDs
- Hidden SSID
- Relay Function
- WiFi Timing ON/OFF
- RF Power Adjustment
- Wireless Client Limitation (Up to 64 Users)
- Intelligent Channel Analysis
- Automatic Optimal Channel Selection

- One-Button Pairing

These features help optimize wireless coverage, improve network efficiency, and simplify deployment.

Wireless Security

Supports:

- NONE (Open)
- WPA/WPA2-PSK (TKIP/AES)
- EAP Authentication

Additional security features include:

- Wireless MAC Address Filtering (Whitelist)
- Wireless Network Isolation
- AP Internal Isolation

These mechanisms help secure wireless communications and control user access.

User Management

Supports wireless client management with:

- Wireless Client Monitoring
- Wireless Client Limitation (Up to 64 Users)

These features help maintain stable wireless performance in multi-user environments.

Device Management

Supports:

- Configuration Backup
- Configuration Restore

- Factory Reset
- Firmware Upgrade
- Scheduled Restart
- Immediate Restart
- Time Synchronization
- System Logging

These tools simplify administration, maintenance, and troubleshooting.

Easy Configuration

The AIRY-WB900-5K supports one-button pairing, AP/Repeater mode selection, intelligent channel analysis, automatic optimal channel selection, and WEB GUI management, helping reduce deployment time and simplify wireless bridge installation.

Logs

Supports System Logs for monitoring, diagnostics, and maintenance activities.

Hardware

Solid Performance with Non-Blocking Architecture

Powerful hardware platform with 128MB DDR2 memory and 16MB Flash, the COMMANDO AIRY-WB900-5K is designed to deliver stable wireless bridge performance and reliable long-distance data transmission. The optimized hardware architecture ensures efficient operation for Point-to-Point and Point-to-Multipoint wireless networking deployments.

Physical Ports and Networking Interfaces

The AIRY-WB900-5K is equipped with high-speed Gigabit Ethernet interfaces for reliable wired connectivity and simplified outdoor installation.

- 1 × 10/100/1000Mbps WAN Port with 12V Passive PoE
- 1 × 10/100/1000Mbps LAN Port
- DC 12V Power Input
- Reset Button
- AP/Repeater Mode Selection Switch
- LED Indicators (SYS, WAN, LAN, 5G WiFi, Signal ×4)

The integrated Passive PoE support enables both power and data transmission through a single Ethernet cable, simplifying deployment in outdoor environments.

High-Gain Directional Antenna System

The AIRY-WB900-5K features a built-in 15dBi high-gain directional antenna designed for long-distance outdoor wireless bridge applications.

- Operating Frequency: 5150MHz – 5850MHz
- Antenna Gain: 15dBi
- Horizontal Beam Angle: 60°

- Vertical Beam Angle: 30°

The directional antenna provides focused signal transmission, helping improve link stability and reduce interference over long-distance wireless connections.

Long-Distance Wireless Bridge Design

Designed for outdoor wireless bridge deployments, the AIRY-WB900-5K supports transmission distances of up to 5KM and is ideal for:

- Building-to-Building Connectivity
- CCTV Surveillance Backhaul
- Campus Networking
- Industrial Networking
- Remote Site Interconnection

Flexible Power Options

Supports multiple power input methods:

- 12~48V Passive PoE
- DC 12V Power Input

These power options provide installation flexibility for various outdoor deployment scenarios.

Reliable Outdoor Operation

Designed for dependable operation under varying environmental conditions.

- Operating Temperature: -20°C to 55°C
- Storage Temperature: -40°C to 70°C
- Humidity: 5%–95% (Non-Condensing)

These specifications help ensure stable operation in demanding outdoor environments.

Industrial-Grade Protection

The AIRY-WB900-5K incorporates built-in protection mechanisms to improve equipment reliability.

- ESD Protection
 - Air: $\pm 8\text{KV}$
 - Touch: $\pm 6\text{KV}$
- Electrical Surge Protection
 - Common Mode: 2KV
 - Differential Mode: 1KV

These protection features help safeguard the device against electrical disturbances commonly encountered in outdoor installations.

Weather-Resistant Outdoor Design

Featuring an IP65-rated enclosure, the AIRY-WB900-5K is designed to withstand harsh outdoor conditions while maintaining reliable wireless bridge performance.

Energy-Efficient Operation

With power consumption of less than 10W, the AIRY-WB900-5K delivers reliable long-distance wireless connectivity while maintaining low energy consumption.

Compact and Lightweight Design

The compact outdoor enclosure enables quick installation and easy deployment.

- Dimensions: 245 x 83 x 43 mm
- Weight: 0.38kg

Its lightweight design simplifies mounting while ensuring durability for long-term outdoor operation.

Specifications

Technical Specifications

The COMMANDO AIRY-WB900-5K is a high-performance 5.8GHz Outdoor Wireless Bridge based on IEEE 802.11ac Wave 2 technology. It supports wireless transmission distances of up to 5KM, features a built-in 15dBi directional antenna, and provides Point-to-Point (P2P) and Point-to-Multipoint (P2MP) connectivity with Gigabit Ethernet interfaces for reliable outdoor wireless networking.

Table 1. Specifications

Technical Parameters	Specification
Model	AIRY-WB900-5K
Wireless Standard	IEEE 802.11a/n/ac Wave 2
Memory	128MB DDR2
Flash	16MB
Frequency Band	5.8GHz
Frequency Range	5150MHz – 5850MHz
Wireless Data Rate	Up to 867Mbps
Wireless Transmission Distance	Up to 5KM
Wireless Deployment Mode	Point-to-Point (P2P), Point-to-Multipoint (P2MP)
Working Mode	AP Mode, Repeater Mode
Maximum Wireless Clients	Up to 64 Users
Multiple SSID	Up to 4 SSIDs
Antenna Type	Built-in Directional Antenna

Technical Parameters	Specification
Antenna Gain	15dBi
Horizontal Beam Angle	60°
Vertical Beam Angle	30°
Hardware Interfaces	1 × 10/100/1000Mbps WAN Port with 12V Passive PoE, 1 × 10/100/1000Mbps LAN Port, DC Power Interface, Reset Button, AP/Repeater Switch
LED Indicators	SYS, WAN, LAN, 5G WiFi, Signal Strength (4 LEDs)
Wireless Security	NONE (Open), WPA/WPA2-PSK (TKIP/AES), EAP Authentication
Access Control Features	Wireless MAC Address Filtering (Whitelist), Wireless Isolation, AP Internal Isolation
Wireless Features	Hidden SSID, Relay Function, WiFi Timing ON/OFF, RF Power Adjustment, Intelligent Channel Analysis, Automatic Optimal Channel Selection, One-Button Pairing
Network Features	DHCP Server, VLAN Configuration
Management	WEB GUI Management
Device Management	Configuration Backup, Configuration Restore, Factory Reset, Firmware Upgrade, Scheduled Restart, Immediate Restart, Time Synchronization, System Log
Power Input	12~48V Passive PoE or DC 12V
Power Consumption	< 10W
Protection Grade	IP65
Dimension (L × W × H)	245 x 83 x 43 mm

Technical Parameters	Specification
Weight	0.38kg
Operating Temperature	-30°C to 55°C
Storage Temperature	-40°C to 70°C
Humidity	5%–95% (Non-Condensing)
ESD Protection	Air: ±8KV, Touch: ±6KV
Electrical Surge Protection	Common Mode: 2KV, Differential Mode: 1KV
Warranty Period	2 Year

Table 2. COMMANDO AIRY-WB900-5K LED Indication

LED Indicator	LED Status
SYS	Blinking: System is operating normally.
WAN	ON/Blinking: WAN port is connected and transmitting data.
LAN	ON/Blinking: LAN port is connected and transmitting data.
5G WiFi	ON/Blinking: 5GHz wireless radio is enabled and wireless activity is present.
Signal * 4	Indicates wireless signal strength level.

Included in the Bundle/Box

COMMANDO AIRY-WB900-5K comes with the following accessories:

- 1 × COMMANDO AIRY-WB900-5K Wireless Bridge (CPE)
- 1 × PoE Adapter
- 2 × Nylon Ties
- 1 × Guide Manual
- 1 × Gift Box

Support and Warranty

- Same-day assistance
- Comprehensive 24-hour support using common communication/chat platforms, Email and Telephone.
- Provide FAQs and troubleshooting help online (self-service) through cloud-based solutions.
- Highly technical and trained representatives to resolve issues.
- Two-year default warranty with option of warranty extension up to 3 years

COMMANDO WarrantyX Program available
on: <https://www.commandonetworks.com/warranty>

Table 3. Support and Warranty

Warranty and Support	
Products covered	COMMANDO AirY 900Mbps, 5.8GHz, 15dBi, 802.11ac Wave 2, P2P/P2MP, 5KM Wireless Bridge
Warranty duration	Two Year RTB (Return To Base) replacement warranty – optionally extendable up to 3 years.
Hardware replacement	COMMANDO, its resellers or its service center will use commercially reasonable efforts to replace the product subject to stock availability. Otherwise, a replacement will be arranged within 15 working days after receipt of the Return Materials Authorization (RMA) request.
End-of-life policy	In case of discontinuation of the product, support is limited to 3 years from announcement date.
Effective date	Hardware warranty commences from the date of shipment to customer (and in case of resale by a COMMANDO reseller, not more than 90 days after original shipment by COMMANDO).
Support duration	Lifetime support.
COMMANDO Care	COMMANDO will provide 24x7 support for basic configuration, diagnosis, and troubleshooting of device-level problems for up to one year from the date of shipment of the originally purchased product. This support does not include solution or network-level support beyond the specific device under consideration.
Online Portal Access	Warranty allows guest access to commandonetworks.com for all available technical queries.

Ordering Information

To place an order, please contact your local reseller/distributor or COMMANDO Sales Representative at www.commandonetworks.com/catalog

Table 4. COMMANDO wireless bridge Ordering Information

Product Code	Product Description
AIRY-WB900-5K	COMMANDO AirY 900Mbps, 5.8GHz, 15dBi, 802.11ac Wave 2, P2P/P2MP, 5KM Wireless Bridge
AIRY-WB900-8K	COMMANDO AirY 900Mbps, 5.8GHz, 18dBi, 802.11ac Wave 2, P2P/P2MP, 8KM Wireless Bridge
AIRY-WB900P-5K	COMMANDO AirY 900Mbps, 5.8GHz, 14dBi, 802.11ac Wave 2, P2P/P2MP, PoE, Disp, 5KM Wireless Bridge
AIRY-WB900-3K	COMMANDO AirY 900Mbps, 5.8GHz, 12dBi, 802.11ac Wave 2, P2P/P2MP, 3KM Wireless Bridge
AIRY-WB300-1K	COMMANDO AirY 300Mbps, 2.4GHz, 6dBi, 802.11n, P2P/P2MP, 1KM Wireless Bridge

Document History

Release	New or Revision	Described in	Date
Release 1	First Release	First Release	July 1st, 2026